



HEAVY DUTY CONSTRUCTION

The Nuhn Heavy Commercial Fill Pipe is the strongest built unit on the market. The main discharge pipe is made from 3/16" thick steel, resulting in longer life of the unit. Consideration was taken for 7000+ GPM volumes, and increased fluid velocities and pressures produced by the Nuhn Header Series Pumps. Heavy construction also increases unit stability, and reduces fill pipe movement resulting from high volumes.

REDUCED FOAMING AT 7000+ GPM

The Nuhn Heavy Commercial Fill Pipe expands to 10" discharge which decreases pressure and fluid velocities by 56%. This allows the operator to fill at maximum speeds, while reducing foaming.

Strategically placed fins stop the fluid from spinning inside the pipe and reduce discharge flare and splashing.



10" FINNED DISCHARGE ELBOW

Reduces splashing and flare resulting from manure spinning while leaving load stand.

12" HINGED DISCHARGE

A 12" lay-flat hose is used to control the manure being discharged into the tank. The hose is attached using a hinge, which allows it to easily drop into a fill port. The hose also has air vents incorporated into it to prevent the hose from causing excessive spilling in between loads.

8" TO 10" EXPANSION

10" Pipe for last 10' of load stand to reduce liquid velocity, resulting in less foam.

3/16" PIPE THICKNESS

Heavier construction allows for a longer life of the unit and makes the load pipe more stable while loading at high volumes. The faster load speed causes more abrasion, and a thicker pipe withstands these higher volumes.

ADDITIONAL FEATURES

The loading pipe has a modular design, a winch for height adjustments and a large diameter tire which increases the stability on uneven terrain.

OPTIONAL HOSE BASKET

Allows for easy transport of discharge hoses and hose accessories. The open design allows for easy cleaning *(Right)*



TECHNICAL SPECIFICATIONS

OVERALL LENGTH	35'
INPUT PIPE DIAMETER	8"
DISCHARGE PIPE DIAMETER	10"
DISCHARGE HOSE DIAMETER	12"
PIPE WALL THICKNESS	3/16"
TIRE SIZE	205/75D15
SPINDLE SIZE	1,500 LBS
HINGED DISCHARGE HOSE	STANDARD
INTERNAL FINS	STANDARD
VENTED DISCHARGE	STANDARD